

KEK Kibblers

Lump Breakers and Pre Breakers



- » Robust design
- » Slow speed / High torque
- » Quick screen changes
- » Hygienic and easy to clean



Strong and robust KEK Kibbler's are designed to grind large lumps of up to (150 mm) and reduce them to (2-3 mm) in preparation for further processing. The lump breaking process takes place through a combination of impact, crushing, cutting and abrasion. While the slow speed, heavy-duty beater, sweeps product against the contoured grinding screen.

FEATURES:

- » Food grade contact parts throughout
- » Food grade metal detectable seals and gaskets
- » Cantilever design
- » Hinged and interlocked access doors
- » Low speed, high torque
- » Various motor configurations
- » Variety of screen and beater configurations
- » Customisable i.e. clean in place / extra hinge doors

COMPLIANCE:

- » EU 1935/2004 and ISO 9001
- » 98/37/EC European Machinery Directive
- » ATEX 2014/34/EU

BENEFITS:

- » Reliable machine for continuous processing and minimum downtime
- » KEK cantilever design minimises maintenance points and increases accessibility
- » Easy clean and hygienic
- » Configurable for a wide range of products, applications and size distributions


APPLICATIONS:


- » Densification of larger particle products
- » Pre break for product rework prior to milling
- » Particle size reduction to create a more easily conveyed product
- » Product rework grinding




KEK Kibblers Data Table

| KEK Kibblers Unit Size | M203 | M303 | M305 | M311 | M505 |
|---|---|------------|------------|--------------------------|--------------------------|
| Cantilever Design ATEX Availability | • | • | • | On request On request | On request On request |
| Typical Unit Dimensions Height (mm) Length (mm) | 350 500 | 450 600 | 490 600 | On request On request | On request On request |
| Approx. Net Weight (kg | 190 | 190 | 420 | On request | On request |
| Motor Size (hp) Motor Size (kW) | 4 3 | 4 3 | 7.5 5.5 | On request On request | On request On request |
| Available Screens | Conidur 1-4 mm, raised lip 5-25 mm, square 5-25 mm Conidur (serrated), square hole, round hole | | | | |







Spares and Servicing are available, to talk to one of our experts please call: +44 (0)1625 412000